

# Redpost Charger/Interface



## Redpost Charger/Interface

### General product information

Through pasteurization, the number of micro-organisms in beer and beverages are reduced and consequently their shelf life increased. To maintain the quality of the product with regard to taste, smell, brightness and color, pasteurization should be a gentle heat treatment. The most commonly used method of pasteurization makes use of a tunnel pasteurizer, through which containers, like glass bottles or cans, travel while being sprayed with warm water. The effect of heat treatment in relation to time is expressed in pasteurization units (PUs).

The Redpost Charger/Interface, type RPC-80, charges the battery of the PU-Monitor and is equipped with a PC and printer interface. The printer interface enables direct printing and working stand-alone. The RPC-80 is compatible with all RPU-Monitors.

After the pasteurizing process is finished, the measurement stops and the PUs are displayed immediately on the PU-Monitor. Connecting it to the RPC-80, it will recognize the monitor and start charging. The measured values can be directly printed and/or passed on to a PC.

The RedLink software processes the measured values and displays it in tabular and graphical format, which can be printed and/or stored.



**RPC-80**

# Redpost Charger/Interface



## Benefits

- Stand-alone system (no PC required)
- Maintenance free

## Applications

- Tunnel pasteurizer
- In combination with all Redpost PU-Monitors

## Technical Data

Charging time:	6 hours (for full charge at 300 series PU-Monitors)
Interfaces:	RS-232, USB for printing
Voltage:	100 - 240 V AC / 50-60 Hz

Dimensions:	310 x 240 x 150 (LxWxH in mm)
Weight:	4.5 kg

## Scope of Supply

- Redpost Charger/Interface, type RPC-80
- PU-Monitor connecting cable
- Mains cable (Euro, US, UK or AUS plug)
- RedLink software set (CD + Interface)
- Printer cable
- Instruction Manual

## Options

- Printer



### Haffmans BV

P.O. Box 3150 NL-5902 RD Venlo, The Netherlands

T +31 77 323 23 00 • F +31 77 323 23 23

E [info@haffmans.nl](mailto:info@haffmans.nl) • I [www.haffmans.nl](http://www.haffmans.nl)

Haffmans BV reserves the right to make changes in the technical specifications at any time.

## RPC-80